

Connector-14PIN


1	Brown
8	Pink
11	BlackGreen
13	Black
3	NavyGreen
4	White
5	NavyBlue
10	Red
12	Blue
7	Purple
6	Gray
2	
9	
14	

Place
On Base Plate


J2	PWR	1
	RTN	2
	RTN	3
	Thermistor	4
	Throttle_AN	5
	Brake_AN	6
	5V Output	7
	Micro_SW	8
	Reverse_SW	9
	Brake_SW	10
	Reserver	11
	Reserver	12
	Reserver	13
	RTN	14

Aviation Plug
J2 on Controller1

Permanent Magnet Motor



Controller 1(1# 控制器)



See From Front Side

1	2	3	4	5	6	7
Brown From battery	NavyGreen Thermistor	White Throttle	NavyBlue Brake_AN	Gray Brake_SW	Purple Reverse_SW	
8	9	10	11	12	13	14
Pink PWR	Red 5V output	BlackGreen SW Common	Blue Micro_SW	Black RTN		

14PIN Connector

PMB(24V-72V) Controller Assembly Wiring Diagram

							KELLY CONTROLS, LLC	
Mark	Subarea	Signatory	Date	04/2011				
Design		Stand		modification	Number	Proportion		
Assessor							V1.1	
Technics		Authorize						
Sum								